



**VOCA<sup>x</sup>**

**Technical specification**

**Table Top**  
 Width: 1000 - 2100 mm  
 Depth: 800 mm

**Velocity**  
 Up to 30 mm/sec

**Borders: telescopic**  
 From 1000 mm to 1800 mm

**Travel range**  
 600 mm

**Frame height**  
 From 617 mm to 1217 mm  
 (Including 31 mm height)

**Table Top side supports**  
 L=480 mm

**Tube dimensions**  
 Rect. tube:  
 80x60, 70x50, 60x40  
 ⚠️ DOWN

**Noise level**  
 < 43 dB

**Feet**  
 Height: 31-41 mm

**Load**  
 Up to 120 kg

**Electronics**

**Control system ECS-2**  
 Control: 2 paralel columns

**Power consumption**  
 Stand by: 0,5 W

**Standards & Environment**  
 Control unit: WEE, CE, FCC, TÜV/GS


**Power unit**  
 Input: 110-240 V  
 Frequency: 50/60 Hz  
 Output: 29 V  
 Power plug: EU

**Operating Environment**  
 Operating cycle 1 min., on, 9 min., off  
 Operating temperature: 10 °C -40 °C (indoors)  
 Operation: 88 - 146 W at 0 - 120 kg load

**Collision detection**  
 On

**Gliding system**  
 Yes

**Control unit reset manual**



**1. Press and hold „UP“ and „DOWN“ simultaneously for 7 seconds**



**2. Lower table to lowest point by pressing „DOWN“ button**

**3. Table is ready to use**

